



Self-checking technology that **ENSURES** operation & accuracy.





DO YOU REALLY KNOW IF YOUR GAS SENSORS ARE WORKING?

TruCal saves time and money by doing the hard work for you



Extend Calibration Intervals

Up to 18 months



Validated Performance

Know that the sensor works between calibrations



Automated Pulse Checks

Defined calibration periods are a thing of the past

Active Technology



Proactive Self-Checks

4x per day



Active Correction

- Adjusts sensor readings due to environmental factors.
- Compensates for maturing sensor performance.



Automatic Notifications

- When calibration is required.
- Sensor End-of-Life is near.

Traditional





CURRENTLY

TruCal®

Pulse Check

Every 6 hours Stimulates XCell sensor with a response similar to having actual calibration gas applied



Proactive Self-Checks (Patented)

AEC AEC

Compares the stimulated response to the last calibration and makes adjustments

Last Calibration SensitivityCurrent Pulse Sensitivity

AEC

ADAPTIVE ENVIRONMENTAL COMPENSATION

...basically, if anything needs to be adjusted after a **Pulse Check**, **AEC** will make the necessary changes automatically and keep you going!



Ensures electrical connectivity to the sensors



Checks for electrode poisoning



Adapts sensitivity for environmental effects like high heat or humidity



The Safety Company

Notifies user if a full span calibration is required

fyi

Other Self-Checking sensors can only do this one action

Validate Recommend Report the life and that the when a full 03 calibration health status as sensor is operating should be "Good" or "Fair". performed. normally. Compensate Warn **Alert** for sensitivity when a sensor the end user that 02 drift due to will need to be the device is no 06 **TruCal**® replaced in the changing longer able to monitor the area. environmental near future. conditions. (2-3 mo) A fault will initiate.

TruCal®
sets a new standard for
RELIABILITY