

# DF2410 SERIES

## Sliding Stem Control Valve



Rugged globe style control valves intended for demanding high pressure and severe service applications in process control.

The compact design makes installation and maintenance more convenient than traditional valve and actuator assemblies.

### Target Markets:

- Oil & Gas
- Gas Transmission

### Product Description

Service:	Liquid/Gas
Size Range:	2 inch
Pressure Range:	ASME 150 - 900/1500
Temperature Range:	-50F to +300F
End Connections:	NPT / RF / RTJ
Standard Materials:	Body: LCC
	Trim: S17400 DH1150 or S31600 Tungsten Carbide
	Seals: HNBR
Operations:	• On/Off                      • Throttling
Features:	Powerful compact design
	Easy maintenance and trim change
	NACE Ready
	Standard live-loaded packing

## How to Order

All orders should be placed with your local Dyna-Flo Control Valve representative.

Our factory trained representatives are experts in:

- Determining valve size
- Identifying the right valve for the application
- Compliance with codes and standards

Visit [www.dynaflo.com/distributors](http://www.dynaflo.com/distributors) to find your local representative.

DF2410 product information is available in the full product catalogue.



While this information is presented in good faith and believed to be accurate, Dyna-Flo Control Valve Services Ltd., division of Curtiss-Wright Flow Control Corporation, does not guarantee satisfactory results from reliance on such information. Nothing contained herein is to be construed as a warranty or guarantee, expressed or implied, regarding the performance, merchantability, fitness or any other matter with respect to the products, nor as a recommendation to use any product or process in conflict with any patent. Dyna-Flo Control Valve Services Ltd., division of Curtiss-Wright Flow Control Corporation, reserves the right, without notice, to alter or improve the designs or specifications of the products described herein.